Amendments to the Claims

Applicants respectfully request reconsideration of this application as amended. Claims 1-51 were pending. Claims 1, 6, 13, 15-16, 19, 21-25, and 28-51 have been amended. No claims have been added. Claims 12, 14, 18, 20, 43, and 45-46 have been canceled without prejudice. Claims 1-11, 13, 15-17, 19, 21-42, 44, and 47-51 remain pending.

Listing of Claims:

1.   (Currently amended) A method in a network access device comprising:

without proxying, analyzing each of a stream of packets traversing a single connection through the network access device from an external host to a protected host;

forwarding each allowed packet of the stream of packets as long as the connection is active, wherein forwarding each allowed packet comprises transmitting a message indicating that each allowed packet is allowed; and

if one of the stream of packets is determined to be disallowed by said analyzing, then discarding the disallowed packet and terminating the connection, causing the protected host to discard those packets received on the terminated connection.

2.   (Original) The method of claim 1 wherein analyzing each of the stream of packets comprises inspecting a header of each of the stream of packets against a packet filter.

3.   (Original) The method of claim 1 wherein analyzing each of the stream of packets comprises inspecting a payload of each of the stream of packets for disallowed content.

4.   (Original) The method of claim 3 wherein inspecting the payload of each of the stream of packets comprises copying the payload, analyzing the payload, and discarding the corresponding packet if the payload is threatening.

5.   (Original) The method of claim 1 further comprising:

      copying a payload from each of a plurality of packets that comprise a file, the

           stream of packets including the plurality of packets;

      forwarding all but the last of the plurality of packets to the protected host;

      reassembling the plurality of packets into the file;

      analyzing the file;

      if the file is a threatening file then discarding the last packet and terminating the

           connection; and

      if the file is non-threatening, then forwarding the last packet.

6.   (Currently amended) A computer implemented method comprising:

      copying a packet payload of each of a plurality of packets received on a single

           connection between an external host and a protected host that carries a

           stream of packets the stream of packets including the plurality of packets;

      forwarding all but the last of the plurality of packets to the protected host;

      reassembling the copied packet payloads into a file;

      analyzing the file to determine if the file is allowed or disallowed;

      <u>maintaining the connection while analyzing the file, said maintaining comprising</u>

           <u>copying each of the plurality of packets but the last packet before</u>

             <u>forwarding each of the plurality of packets, and</u>

holding the last packet and repeatedly forwarding the last copied packet;

if the file is allowed, then forwarding the last packet to the protected host; and

if the file is determined to be disallowed, then dropping the last packet and

terminating the connection.

7.   (Original) The computer implemented method of claim 6 wherein the analyzing

the file comprises performing anti-virus analysis on the file.

8.   (Original) The computer implemented method of claim 6 further comprising:

analyzing a header of each of the stream of packets; and

if one of the stream of packets is determined to be disallowed, then discarding the

disallowed packet and terminating the connection.

9.   (Original) The computer implemented method of claim 8 wherein analyzing the

header comprises inspecting addresses indicated in the header against a packet filter.

10.   (Original) The computer implemented method of claim 6 further comprising:

individually analyzing each of the copied packet payloads; and

if one of the copied packet payloads is determined to be threatening, then

discarding the corresponding packet and terminating the connection.

11.   (Original) The computer implemented method of claim 10 wherein analyzing

each of the copied packet payloads comprises inspecting each copied packet payload

against a list of disallowed content and determining if each copied packet payload

includes threatening script.

12.   (Canceled).

13. (Currently amended) A [[The]] computer implemented method comprising: of
claim 12

> copying a packet payload of each of a plurality of packets received on a single
>
>> connection between an external host and a protected host that carries a
>>
>> stream of packets the stream of packets including the plurality of packets;
>
> forwarding all but the last of the plurality of packets to the protected host;
>
> reassembling the copied packet payloads into a file;
>
> analyzing the file to determine if the file is allowed or disallowed;
>
> maintaining the connection while analyzing the file, wherein maintaining the
>
>> connection comprises:
>>
>> decapsulating the last packet's payload[[;]],
>>
>> fragmenting the last packet's payload into subparts[[;]],
>>
>> encapsulating each subpart[[;]], and
>>
>> forwarding each subpart until analysis is complete;
>
> if the file is allowed, then forwarding the last packet to the protected host; and
>
> if the file is determined to be disallowed, then dropping the last packet and
>
>> terminating the connection.

14. (Canceled).

15. (Currently amended) The computer implemented method of claim [[12]] 6,
wherein maintaining the connection comprises increasing transmission latency of each
acknowledgement transmitted from the protected host to the external host until the
analysis is complete.

16.   (Currently amended) A [[The]] computer implemented method comprising: of ~~claim 6~~

copying a packet payload of each of a plurality of packets received on a single
        connection between an external host and a protected host that carries a
        stream of packets the stream of packets including the plurality of packets;

forwarding all but the last of the plurality of packets to the protected host;

reassembling the copied packet payloads into a file;

analyzing the file to determine if the file is allowed or disallowed;

if the file is allowed, then forwarding the last packet to the protected host, wherein
        forwarding each of the plurality of packets comprises transmitting a
        message indicating that each of the of the plurality of packets is allowed;
        and

if the file is determined to be disallowed, then dropping the last packet and
        terminating the connection.

17.   (Currently amended) A computer implemented method comprising:

supporting a connection from an external host to a protected host;

analyzing a header of each packet received over the connection from the external
        host;

terminating the connection if a first packet received over the connection is
        determined to be disallowed and discarding the first packet;

if the connection is not terminated, copying the first packet's payload;

analyzing the first packet's payload;

terminating the connection if said first packet's payload is determined to be
        disallowed and discarding the first packet;

if the connection has not been terminated and if said first packet's payload is not a
        last block of a file, then forwarding said first packet to the protected host;

if said first packet's payload is the last block of a file, then reassembling the first

packet's payload with a set of one or more previously copied packet

payloads into the file;

analyzing the file to determine if the file is allowed or disallowed;

maintaining the connection while analyzing the file, said maintaining comprising

copying each of the plurality of packets but the last packet before

forwarding each of the plurality of packets, and

holding the last packet and repeatedly forwarding the last copied packet;

if the file is disallowed then dropping the first packet and terminating the

connection; and

if the file is allowed then forwarding the first packet.

18.   (Canceled).

19.   (Currently amended) A [[The]] computer implemented method comprising: of
claim 18

supporting a connection from an external host to a protected host;

analyzing a header of each packet received over the connection from the external

host;

terminating the connection if a first packet received over the connection is

determined to be disallowed and discarding the first packet;

if the connection is not terminated, copying the first packet's payload;

analyzing the first packet's payload;

terminating the connection if said first packet's payload is determined to be

disallowed and discarding the first packet;

if the connection has not been terminated and if said first packet's payload is not a

last block of a file, then forwarding said first packet to the protected host;

if said first packet's payload is the last block of a file, then reassembling the first

packet's payload with a set of one or more previously copied packet

payloads into the file;

analyzing the file to determine if the file is allowed or disallowed;

maintaining the connection while analyzing the file, wherein maintaining the

connection comprises:

decapsulating the last packet's payload[[;]],

fragmenting the last packet's payload into subparts[[;]],

encapsulating each subpart[[;]], and

forwarding each subpart until analysis is complete;

if the file is disallowed then dropping the first packet and terminating the

connection; and

if the file is allowed then forwarding the first packet.

20.   (Canceled).

21.   (Currently amended) The computer implemented method of claim 17, [[18]]
wherein maintaining the connection comprises increasing transmission latency of each
acknowledgement transmitted from the protected host to the external host until the
analysis is complete.

22.   (Currently amended) The computer implemented method of claim [[6]] 17
wherein the analyzing the file comprises performing anti-virus analysis on the file.

23.   (Currently amended) The computer implemented method of claim [[8]] 17
wherein analyzing the header comprises inspecting addresses indicated in the header
against a packet filter.

24.   (Currently amended) The computer implemented method of claim [[10]] 17, wherein analyzing the first packet's payload ~~each of the copied packet payloads~~ comprises inspecting the first packet's ~~each copied packet~~ payload against a list of disallowed content and determining if the first packet's ~~each copied packet~~ payload includes threatening script.

25.   (Currently amended) An apparatus comprising:

>   a forwarding module to forward packets of a datastream along a connection between a protected host and an external host; and

>   a datastream analysis module coupled with the forwarding module, the datastream analysis module to analyze each of the packets to determine if each of the packets are allowed or disallowed and to terminate the connection upon determining one of the packets to be disallowed and to discard the disallowed packet, causing the protected host to discard packets received on the terminated connection prior to the disallowed packet, wherein the forwarding module is operable to maintain the connection while the analysis module is analyzing the packets by copying each of the packets but the last packet before forwarding each of the packets, and holding the last packet and repeatedly forwarding the last copied packet.

26.   (Original) The apparatus of claim 25 further comprising a memory to store each of the packets until forwarded or discarded.

27.   (Original) The apparatus of claim 25 further comprising a memory coupled with the datastream analysis module, the memory to store copies of each of the packets' payloads.

28.   (Currently amended) A ~~machine-readable medium~~ physical machine-~~accessible~~ *readable* storage medium that provides instructions, which when executed by a set of one or more processors, cause said set of processors to perform operations comprising:

without proxying, analyzing each of a stream of packets traversing a single connection through the network access device from an external host to a protected host;

forwarding each allowed packet of the stream of packets as long as the connection is active, wherein forwarding each allowed packet comprises transmitting a message indicating that each allowed packet is allowed; and

if one of the stream of packets is determined to be disallowed by said analyzing, then discarding the disallowed packet and terminating the connection, causing the protected host to discard those packets received on the terminated connection.

29.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ *readable* storage medium of claim 28 wherein analyzing each of the stream of packets comprises inspecting a header of each of the stream of packets against a packet filter.

6/6/07
AH

30.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ *readable* storage medium of claim 28 wherein analyzing each of the stream of packets comprises inspecting a payload of each of the stream of packets for disallowed content.

31.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ *readable* storage medium of claim 30 wherein inspecting the payload of each of the stream of packets comprises copying the payload, analyzing the payload, and discarding the corresponding packet if the payload is threatening.

32.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ ^{readable} storage medium of claim 28 further comprising:

copying a payload from each of a plurality of packets that comprise a file, the

stream of packets including the plurality of packets;

forwarding all but the last of the plurality of packets to the protected host;

reassembling the plurality of packets into the file;

analyzing the file;

if the file is a threatening file then discarding the last packet and terminating the

connection; and

if the file is non-threatening, then forwarding the last packet.

6/6/07

AH

33.   (Currently amended) A ~~machine-readable medium~~ physical machine-~~accessible~~ readable storage medium that provides instructions, which when executed by a set of one or more

processors, cause said set of processors to perform operations comprising:

copying a packet payload of each of a plurality of packets received on a single

connection between an external host and a protected host that carries a

stream of packets the stream of packets including the plurality of packets;

forwarding all but the last of the plurality of packets to the protected host, wherein

forwarding each of the plurality of packets comprises transmitting a

message indicating that each of the of the plurality of packets is allowed;

reassembling the copied packet payloads into a file;

analyzing the file to determine if the file is allowed or disallowed;

if the file is allowed, then forwarding the last packet to the protected host; and

if the file is determined to be disallowed, then dropping the last packet and

terminating the connection.

34.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ readable storage medium of claim 33 wherein the analyzing the file comprises performing anti-virus analysis on the file.

35.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ readable storage medium of claim 33 further comprising:

    analyzing a header of each of the stream of packets; and

    if one of the stream of packets is determined to be disallowed, then discarding the

        disallowed packet and terminating the connection.

36.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ readable storage medium of claim 35 wherein analyzing the header comprises inspecting addresses indicated in the header against a packet filter.

6/6/07
rH

37.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ readable storage medium of claim 33 further comprising:

    individually analyzing each of the copied packet payloads; and

    if one of the copied packet payloads is determined to be threatening, then

        discarding the corresponding packet and terminating the connection.

38.   (Currently amended) The ~~machine-readable medium~~ physical machine-~~accessible~~ readable storage medium of claim 37 wherein analyzing each of the copied packet payloads comprises inspecting each copied packet payload against a list of disallowed content and determining if each copied packet payload includes threatening script.

39.   (Currently amended) The ~~machine-readable medium~~ physical machine-accessible *readable* storage medium of claim 33 further comprising maintaining the connection while analyzing the file.

40.   (Currently amended) ~~The machine-readable medium~~ A physical machine-*readable* accessible storage medium that provides instructions, which when executed by a set of one or more processors, cause said set of processors to perform operations comprising: ~~of claim 39~~

copying a packet payload of each of a plurality of packets received on a single connection

between an external host and a protected host that carries a stream of packets the

stream of packets including the plurality of packets;

forwarding all but the last of the plurality of packets to the protected host;

reassembling the copied packet payloads into a file;

analyzing the file to determine if the file is allowed or disallowed;

maintaining the connection while analyzing the file, wherein maintaining the connection

comprises:

decapsulating the last packet's payload[[;]],

fragmenting the last packet's payload into subparts[[;]],

encapsulating each subpart[[;]], and

forwarding each subpart until analysis is complete;

if the file is allowed, then forwarding the last packet to the protected host; and

if the file is determined to be disallowed, then dropping the last packet and terminating

the connection.

6/6/07

AH

41.   (Currently amended) ~~The machine-readable medium~~ A physical machine-*readable* accessible storage medium that provides instructions, which when executed by a set of

one or more processors, cause said set of processors to perform operations comprising: of
~~claim 39~~

copying a packet payload of each of a plurality of packets received on a single connection

between an external host and a protected host that carries a stream of packets the

stream of packets including the plurality of packets;

forwarding all but the last of the plurality of packets to the protected host;

reassembling the copied packet payloads into a file;

analyzing the file to determine if the file is allowed or disallowed;

maintaining the connection while analyzing the file, wherein maintaining the connection

comprises:

copying each of the plurality of packets but the last packet before forwarding each

of the plurality of packets[[;]], and

holding the last packet and repeatedly forwarding the last copied packet;

if the file is allowed, then forwarding the last packet to the protected host; and

if the file is determined to be disallowed, then dropping the last packet and

terminating the connection.

42.   (Currently amended) The ~~machine-readable medium~~ physical machine-accessible *readable*

storage medium of claim 39 wherein maintaining the connection comprises increasing

transmission latency of each acknowledgement transmitted from the protected host to the   *6/6/07*

external host until the analysis is complete.   *M/H*

43.   (Canceled).

44.   (Currently amended) A ~~machine-readable medium~~ physical machine-accessible *readable*

storage medium that provides instructions, which when executed by a set of one or more

processors, cause said set of processors to perform operations comprising:

supporting a connection from an external host to a protected host;

analyzing a header of each packet received over the connection from the external

host;

terminating the connection if a first packet received over the connection is

determined to be disallowed and discarding the first packet;

if the connection is not terminated, copying the first packet's payload;

analyzing the first packet's payload;

terminating the connection if said first packet's payload is determined to be

disallowed and discarding the first packet;

if the connection has not been terminated and if said first packet's payload is not a

last block of a file, then forwarding said first packet to the protected host;

if said first packet's payload is the last block of a file, then reassembling the first

packet's payload with a set of one or more previously copied packet

payloads into the file;

analyzing the file to determine if the file is allowed or disallowed;

maintaining the connection while analyzing the file, said maintaining comprising

decapsulating the last packet's payload,

fragmenting the last packet's payload into subparts,

encapsulating each subpart, and

forwarding each subpart until analysis is complete;

if the file is disallowed then dropping the first packet and terminating the

connection; and

if the file is allowed then forwarding the first packet.

45.   (Canceled).

46.   (Canceled).

47.   (Currently amended) ~~The machine-readable medium~~ A physical machine-
~~readable~~ ~~accessible~~ storage medium that provides instructions, which when executed by a set of

one or more processors, cause said set of processors to perform operations comprising: ~~of~~

~~claim 45~~

> supporting a connection from an external host to a protected host;
>
> analyzing a header of each packet received over the connection from the external
>
>> host;
>
> terminating the connection if a first packet received over the connection is
>
>> determined to be disallowed and discarding the first packet;
>
> if the connection is not terminated, copying the first packet's payload;
>
> analyzing the first packet's payload;
>
> terminating the connection if said first packet's payload is determined to be
>
>> disallowed and discarding the first packet;
>
> if the connection has not been terminated and if said first packet's payload is not a
>
>> last block of a file, then forwarding said first packet to the protected host;
>
> if said first packet's payload is the last block of a file, then reassembling the first
>
>> packet's payload with a set of one or more previously copied packet
>>
>> payloads into the file;
>
> analyzing the file to determine if the file is allowed or disallowed;
>
> maintaining the connection while analyzing the file, wherein maintaining the
>
>> connection comprises:
>>
>>> copying each of the plurality of packets but the last packet before
>>>
>>>> forwarding each of the plurality of packets[[;]], and
>>>
>>> holding the last packet and repeatedly forwarding the last copied packet;
>>
>> if the file is disallowed then dropping the first packet and terminating the
>>
>>> connection; and

if the file is allowed then forwarding the first packet.

48.   (Currently amended) The ~~machine-readable medium~~ physical machine-accessible *readable* storage medium of claim [[45]] 44, wherein maintaining the connection comprises increasing transmission latency of each acknowledgement transmitted from the protected host to the external host until the analysis is complete.

49.   (Currently amended) The ~~machine-readable medium~~ physical machine-accessible *readable* storage medium of claim [[33]] 44 wherein the analyzing the file comprises performing anti-virus analysis on the file.

50.   (Currently amended) The ~~machine-readable medium~~ physical machine-accessible *readable* storage medium of claim [[35]] 44 wherein analyzing the header comprises inspecting addresses indicated in the header against a packet filter.

51.   (Currently amended) The ~~machine-readable medium~~ physical machine-accessible *readable* storage medium of claim [[37]] 44 wherein analyzing the first packet's payload ~~each of the copied packet payloads~~ comprises inspecting the first packet's ~~each copied packet~~ payload against a list of disallowed content and determining if the first packet's ~~each copied packet~~ payload includes threatening script.

6/6/07 /p